



新普科技股份有限公司
 新世電子(常熟)有限公司
 新普科技(重慶)有限公司
 兆普電子(上海)有限公司

Control Number : SACU1205002

UN38.3 Test Report

Recommendations on the TRANSPORT OF DANGEROUS GOODS

(Manual of Tests and Criteria, Fifth revised edition)

Customer : ACER

Model : AL12A72

Rating : 14.8V, 2500mAh / 37Wh

| Approved By | Checked By | Prepared By |
|-------------|-------------|-------------|
| | <i>Sing</i> | <i>Wave</i> |

SIMPLO TECHNOLOGY CO., LTD.

ADD : No.471,Sec.2,Pa Teh Rd.,Hu Kou,Hsin Chu,Hsien 303 Taiwan

TEL: +886-3-5695920

FAX: +886-3-5695931



SIMPLO ELECTRONICS (Changshu) ,LTD.

ADD : No.2 Dong Nan Road,Changshu, Jingsu Province.China

TEL: +86-512-52302255

FAX: +86-512-52302277



SIMPLO ELECTRONICS (CHONGQING) ,LTD.

ADD : No.2 Zongbao Avenue, Shapingba Distnct, Chongqing, China

TEL: +86-23-61718899

FAX: +86-23-61210488



SIMPLO ELECTRONICS (SHANGHAI) ,LTD.

ADD : No.28, Sanzhuang Road., Songjiang Export Processing Zone ,Shanghai

TEL: +86-21-57748286

FAX: +86-21-57748285



本資料為新普科技股份有限公司之智慧財產權，非經本公司書面授權許可，不得透露或使用本資料，亦不得複印、複製或轉變成其它任何形式使用。
 The information contained herein is the exclusive property of SIMPLO TECHNOLOGY CO., LTD, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission.

本測試報告僅對上述測試項目有效,本報告分離使用無效
 This test report is valid only to the items, Invalid for separation using.



1. Purpose of the Test :


To test each cell/battery is of the type proved to meet the requirements in the Recommendations on the TRANSPORT OF DANGEROUS GOODS, Manual of Tests and Criteria, Fifth revised edition.

2. Test Quantity :

- 2.1 Four batteries, at first cycle, in fully charged states. (T.1~T.5 test only)
- 2.2 Four batteries, after fifty cycles ending in fully charged states. (T.1~T.5 test only)
- 2.3 Five component cells, at first cycle at 50% of the design rated capacity. (T.6 test only)
- 2.4 Four batteries, at first cycle, in fully charged states. (T.7 test only)
- 2.5 Four batteries, after fifty cycles ending in fully charged states. (T.7 test only)

3. Test procedure :

- 4.1 All detail related test procedure shall be follow Standard Operation Procedure of SMP subjected CW01-5916 Rev.2 issue documentation.
- 4.2 Test flow shall be follow below statement.





新普科技股份有限公司
新世電子(常熟)有限公司
新普科技(重慶)有限公司
兆普電子(上海)有限公司

Control Number : SACU1205002

4. Test Result :

4.1 T.1 ~T4 Test results: **Pass**

5.1.1 Batteries meet requirement regard mass loss was less then 0.1% and voltage loss less 10% relating original situation.

5.1.2 No leakage, No venting, No disassembly, No rupture and no fire.

4.2 T.5 Test result: **Pass**

5.2.1 All Batteries can meet requirement subjected external temperature does not exceed 170°C.

5.2.2 All Batteries no disassembly, no rupture and no fire within six hours

4.3 T.6 Test results: **Pass**

5.3.1 All cells can meet requirement subjected external temperature does not exceed 170°C.

5.3.2 All cells no disassembly and no fire within six hours of this test.

4.4 T.7 Test results: **Pass**

5.4.1 All batteries can meet no disassembly and no fire within seven days of the test.

All detail evidence will be confirmed follow appendix described.



新普科技股份有限公司
 新世電子(常熟)有限公司
 新普科技(重慶)有限公司
 兆普電子(上海)有限公司

Control Number : SACU1205002

5. Test Equipment :

| SMP | | SIMPLO TECHNOLOGY CO., LTD. | | | Revised date: 2012-03-05 | | Page: | |
|---|---------------|-----------------------------|-------------------------|-------------------------|--------------------------|-----------------------|-----------------------|---------|
| Address : No. 471, Sec.2, Pa Teh Rd., Hu Kou, Hsin Chu Hsien 303 Taiwan | | | | | Date: 2012-05-15 | | | |
| TEL: +886-3-5695920; FAX: +886-3-5695931 | | | | | Project No.: AL12A 4S1P | | | |
| Test Instruments Reference List | | | | | | | | |
| Used | Instrument ID | Instrument Name | Type | Range Used | Manufacturer | Calibration Date_Last | Calibration Date_Next | Remarks |
| Pretest | | | | | | | | |
| V | ML-052 | Learning | 711 | 0~18V 0~8A | SMP | 2011-03-11 | 2012-03-11 | |
| V | ML-053 | Learning | 711 | 0~18V 0~8A | SMP | 2011-03-14 | 2012-03-14 | |
| V | M6-055 | Learning | 711 | 0~18V 0~8A | SMP | 2011-03-14 | 2012-03-14 | |
| T.1 Altitude Simulation | | | | | | | | |
| V | ML-308 | Altitude | | Kpa:30~90 | HSIN JIANG | 2011-09-28 | 2012-09-28 | |
| V | ML-257 | Multimeter | HP 34401A | Note 1 | Agilent | 2012-01-20 | 2013-01-20 | |
| V | ML-494 | Electronic Balance | XS1220M-SCS | 1-1000 gf | CHUANHUA | 2011-09-28 | 2012-09-28 | |
| V | ML-550 | Data logger | 313 | 15~35 °C; 30~80 %RH | CENTER | 2011-12-21 | 2012-12-21 | |
| T.2 Thermal Test | | | | | | | | |
| V | ML-018 | Thermal Shock | WSF-602 | T:-40 to 120°C | WIT | 2011-03-11 | 2012-03-11 | |
| V | ML-257 | Multimeter | HP 34401A | note 1 | Agilent | 2012-01-20 | 2013-01-20 | |
| V | ML-494 | Electronic Balance | XS1220M-SCS | 1-1000 gf | CHUANHUA | 2011-09-28 | 2012-09-28 | |
| T.3 Vibration | | | | | | | | |
| V | ML-233 | Vibration | KD-9636-EM-300F2K-30N80 | F:5~2000Hz G:0.2~20G | King Design | 2012-01-07 | 2013-01-07 | |
| V | ML-257 | Multimeter | HP 34401A | note 1 | Agilent | 2012-01-20 | 2013-01-20 | |
| V | ML-494 | Electronic Balance | XS1220M-SCS | 1-1000 gf | CHUANHUA | 2011-09-28 | 2012-09-28 | |
| V | ML-552 | Data logger | 313 | 15~35 °C; 30~80 %RH | CENTER | 2011-12-21 | 2012-12-21 | |
| T.4 Shock | | | | | | | | |
| V | ML-056 | Shock | DP-1200-25 | G:10~600G | King Design | 2012-01-07 | 2013-01-07 | |
| V | ML-257 | Multimeter | HP 34401A | note 1 | Agilent | 2012-01-20 | 2013-01-20 | |
| V | ML-494 | Electronic Balance | XS1220M-SCS | 1-1000 gf | CHUANHUA | 2011-09-28 | 2012-09-28 | |
| V | ML-551 | Data logger | 313 | 15~35 °C; 30~80 %RH | CENTER | 2011-12-21 | 2012-12-21 | |
| T.5 External Short Circuit | | | | | | | | |
| V | ML-534 | mΩ Hitester | 3540 | 1mΩ ~ 30kΩ | HIOKI | 2011-12-02 | 2012-12-02 | |
| V | ML-339 | Data Acquisition | MX100-E-1D | 1-100 Vdc, -50 to 150°C | Yokogawa | 2012-01-13 | 2013-01-13 | |
| V | ML-010 | chamber | WIT IPC-1000 | -20 to 150°C | WIT | 2011-03-11 | 2012-03-11 | |
| T.6 Impact (Component cell) | | | | | | | | |
| V | ML-340 | Data Acquisition | MX100-E-1D | 1-100 Vdc, -50 to 150°C | Yokogawa | 2011-05-26 | 2012-05-26 | |
| V | ML-076 | Impact tester | | | 吉勝 | 2011-03-11 | 2012-03-11 | |
| T.7 Overcharge | | | | | | | | |
| V | ML-139 | Power Supply | GC50-30D | 0~50V 0.1~30A | LOCK | 2012-03-04 | 2013-03-04 | |
| V | ML-140 | Power Supply | GC50-30D | 0~50V 0.1~30A | LOCK | 2012-03-04 | 2013-03-04 | |
| V | ML-141 | Power Supply | GC50-30D | 0~50V 0.1~30A | LOCK | 2012-03-04 | 2013-03-04 | |
| V | ML-142 | Power Supply | GC50-30D | 0~50V 0.1~30A | LOCK | 2012-03-04 | 2013-03-04 | |
| V | ML-143 | Power Supply | GC50-30D | 0~50V 0.1~30A | LOCK | 2012-03-04 | 2013-03-04 | |
| V | ML-550 | Data logger | 313 | 15~35 °C; 30~80 %RH | CENTER | 2011-12-21 | 2012-12-21 | |
| Note 1: DC Voltage: 0.1-1000V; AC Voltage: 0.5-700V at 60Hz, 1kHz; Resistance: 10Ω-10MΩ; DC Current: 0.1mA-3A; AC Current: 0.01-3A at 60Hz, 0.01-1A, at 1kHz. | | | | | | | | |

本資料為新普科技股份有限公司之智慧財產權，非經本公司書面授權許可，不得透露或使用本資料，亦不得複印、複製或轉變成其它任何形式使用。
 The information contained herein is the exclusive property of SIMPLO TECHNOLOGY CO., LTD, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission.

本測試報告僅對上述測試項目有效，本報告分離使用無效
 This test report is valid only to the items, Invalid for separation using.



新普科技股份有限公司
 新世電子(常熟)有限公司
 新普科技(重慶)有限公司
 兆普電子(上海)有限公司

Control Number : SACU1205002

6. T.1~T7 detail reports:

| Control No.: SACU-1205002 | | UN 38.3 Test Datasheet | | | | | | | |
|--------------------------------|------------|---|----------------------|----------------------------|-------------------------|-----------------|------------|------------------------|---------|
| Customer:ACER | | Model name: AL12A 4S1P | | Test duration: 05-12~05-29 | | Reviewer:Esmond | | | |
| Test Sample identification: | | | | | | | | | |
| Used | Sample No. | Sample state | Used | Sample No. | Sample state | Used | Sample No. | Sample state | |
| V | 1~4 | 1 Cycle, Fully charged | V | 5~8 | 50 Cycle, Fully charged | | | 25Cycle, Fully charged | |
| V | 9~10 | 1 Cycle, Fully charged | V | 13~16 | 50 Cycle, Fully charged | | | 25Cycle, Fully charged | |
| V | 1~5 | 1 Cycle, 50% charged | V | 6~10 | 1 Cycle, 50% charged | | | | |
| T.1 Altitude Simulation | | Start time: 5/12/ 08 : 42 Finish time: 5/12/ 14 : 43 | | Ambient temp.: 21.5 °C | | Operator :Betty | | Reviewer:Esmond | |
| Sample No.: 01 | | | | Sample No.: 02 | | | | | |
| | Before | After | variation | Results | | Before | After | variation | Results |
| Mass (g) | 234.6 | 234.6 | Mass loss % 0.00% | P | Mass (g) | 234.7 | 234.7 | Mass loss % 0.00% | P |
| OCV (V) | 16.62 | 16.61 | Remained OCV% 99.94% | | OCV (V) | 16.63 | 16.61 | Remained OCV% 99.88% | |
| Sample No.: 03 | | | | Sample No.: 04 | | | | | |
| | Before | After | variation | Results | | Before | After | variation | Results |
| Mass (g) | 234.4 | 234.4 | Mass loss % 0.00% | P | Mass (g) | 234.4 | 234.4 | Mass loss % 0.00% | P |
| OCV (V) | 16.63 | 16.61 | Remained OCV% 99.88% | | OCV (V) | 16.64 | 16.62 | Remained OCV% 99.88% | |
| Sample No.: 05 | | | | Sample No.: 06 | | | | | |
| | Before | After | variation | Results | | Before | After | variation | Results |
| Mass (g) | 234.6 | 234.6 | Mass loss % 0.00% | P | Mass (g) | 234.6 | 234.6 | Mass loss % 0.00% | P |
| OCV (V) | 16.62 | 16.61 | Remained OCV% 99.94% | | OCV (V) | 16.63 | 16.62 | Remained OCV% 99.94% | |
| Sample No.: 07 | | | | Sample No.: 08 | | | | | |
| | Before | After | variation | Results | | Before | After | variation | Results |
| Mass (g) | 234.3 | 234.3 | Mass loss % 0.00% | P | Mass (g) | 234.3 | 234.3 | Mass loss % 0.00% | P |
| OCV (V) | 16.64 | 8.25 | Remained OCV% 49.58% | | OCV (V) | 16.63 | 16.61 | Remained OCV% 99.88% | |
| T.2 Thermal Test | | Start time: 5/12/ 15 : 36 Finish time: 5/19/ 11 : 22 | | Ambient temp.: 22.3 °C | | Operator :Betty | | Reviewer:Esmond | |
| Sample No.: 01 | | | | Sample No.: 02 | | | | | |
| | Before | After | variation | Results | | Before | After | variation | Results |
| Mass (g) | 234.6 | 234.6 | Mass loss % 0.00% | P | Mass (g) | 234.7 | 234.7 | Mass loss % 0.00% | P |
| OCV (V) | 16.61 | 16.36 | Remained OCV% 98.49% | | OCV (V) | 16.61 | 16.38 | Remained OCV% 98.62% | |
| Sample No.: 03 | | | | Sample No.: 04 | | | | | |
| | Before | After | variation | Results | | Before | After | variation | Results |
| Mass (g) | 234.4 | 234.4 | Mass loss % 0.00% | P | Mass (g) | 234.4 | 234.4 | Mass loss % 0.00% | P |
| OCV (V) | 16.61 | 16.40 | Remained OCV% 98.74% | | OCV (V) | 16.62 | 16.37 | Remained OCV% 98.50% | |
| Sample No.: 05 | | | | Sample No.: 06 | | | | | |
| | Before | After | variation | Results | | Before | After | variation | Results |
| Mass (g) | 234.6 | 234.6 | Mass loss % 0.00% | P | Mass (g) | 234.6 | 234.6 | Mass loss % 0.00% | P |
| OCV (V) | 16.61 | 16.38 | Remained OCV% 98.62% | | OCV (V) | 16.62 | 16.41 | Remained OCV% 98.74% | |
| Sample No.: 07 | | | | Sample No.: 08 | | | | | |
| | Before | After | variation | Results | | Before | After | variation | Results |
| Mass (g) | 234.3 | 234.3 | Mass loss % 0.00% | P | Mass (g) | 234.3 | 234.3 | Mass loss % 0.00% | P |
| OCV (V) | 8.25 | 8.04 | Remained OCV% 97.45% | | OCV (V) | 16.61 | 16.35 | Remained OCV% 98.43% | |
| T.3 Vibration | | Start time: 5/19/ 14 : 17 Finish time: 5/20/ 16 : 52 | | Ambient temp.: 22.3 °C | | Operator :Betty | | Reviewer:Esmond | |
| Sample No.: 01 | | | | Sample No.: 02 | | | | | |
| | Before | After | variation | Results | | Before | After | variation | Results |
| Mass (g) | 234.6 | 234.6 | Mass loss % 0.00% | P | Mass (g) | 234.7 | 234.7 | Mass loss % 0.00% | P |
| OCV (V) | 16.36 | 16.32 | Remained OCV% 99.76% | | OCV (V) | 16.38 | 16.35 | Remained OCV% 99.82% | |
| Sample No.: 03 | | | | Sample No.: 04 | | | | | |
| | Before | After | variation | Results | | Before | After | variation | Results |
| Mass (g) | 234.4 | 234.4 | Mass loss % 0.00% | P | Mass (g) | 234.4 | 234.4 | Mass loss % 0.00% | P |
| OCV (V) | 16.40 | 16.37 | Remained OCV% 99.82% | | OCV (V) | 16.37 | 16.35 | Remained OCV% 99.88% | |
| Sample No.: 05 | | | | Sample No.: 06 | | | | | |
| | Before | After | variation | Results | | Before | After | variation | Results |
| Mass (g) | 234.6 | 234.6 | Mass loss % 0.00% | P | Mass (g) | 234.6 | 234.6 | Mass loss % 0.00% | P |
| OCV (V) | 16.38 | 16.35 | Remained OCV% 99.82% | | OCV (V) | 16.41 | 16.39 | Remained OCV% 99.88% | |
| Sample No.: 07 | | | | Sample No.: 08 | | | | | |
| | Before | After | variation | Results | | Before | After | variation | Results |
| Mass (g) | 234.3 | 234.3 | Mass loss % 0.00% | P | Mass (g) | 234.3 | 234.3 | Mass loss % 0.00% | P |
| OCV (V) | 8.04 | 8.01 | Remained OCV% 99.63% | | OCV (V) | 16.35 | 16.30 | Remained OCV% 99.63% | |

本資料為新普科技股份有限公司之智慧財產權，非經本公司書面授權許可，不得透露或使用本資料，亦不得複印、複製或轉變成其它任何形式使用。
 The information contained herein is the exclusive property of SIMPLO TECHNOLOGY CO., LTD, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission.

本測試報告僅對上述測試項目有效，本報告分離使用無效
 This test report is valid only to the items, Invalid for separation using.



新普科技股份有限公司
 新世電子(常熟)有限公司
 新普科技(重慶)有限公司
 兆普電子(上海)有限公司

Control Number : SACU1205002

| T.4 Shock | | | | Start time: 5/21/ 08 : 32 | Finish time: 5/22/ 11 : 27 | Ambient temp.: 21.6 ℃ | Operator :Betty | Reviewer:Esmond | | | | | | | | |
|---|----------------|----------------|----------------|---------------------------|----------------------------|-----------------------|-----------------|-----------------|---------------|--------|-------|------|-------|------|-------|------|
| Sample No.: 01 | | | | Sample No.: 02 | | | | | | | | | | | | |
| | Before | After | variation | Results | | Before | After | variation | Results | | | | | | | |
| Mass(g) | 234.6 | 234.6 | Mass loss % | 0.00% | P | Mass(g) | 234.7 | 234.7 | Mass loss % | 0.00% | P | | | | | |
| OCV(V) | 16.32 | 16.29 | Remained OCV% | 99.82% | | OCV(V) | 16.35 | 16.32 | Remained OCV% | 99.82% | | | | | | |
| Sample No.: 03 | | | | Sample No.: 04 | | | | | | | | | | | | |
| | Before | After | variation | Results | | Before | After | variation | Results | | | | | | | |
| Mass(g) | 234.4 | 234.4 | Mass loss % | 0.00% | P | Mass(g) | 234.4 | 234.4 | Mass loss % | 0.00% | P | | | | | |
| OCV(V) | 16.37 | 16.35 | Remained OCV% | 99.88% | | OCV(V) | 16.35 | 16.33 | Remained OCV% | 99.88% | | | | | | |
| Sample No.: 05 | | | | Sample No.: 06 | | | | | | | | | | | | |
| | Before | After | variation | Results | | Before | After | variation | Results | | | | | | | |
| Mass(g) | 234.6 | 234.6 | Mass loss % | 0.00% | P | Mass(g) | 234.6 | 234.6 | Mass loss % | 0.00% | P | | | | | |
| OCV(V) | 16.35 | 16.33 | Remained OCV% | 99.88% | | OCV(V) | 16.39 | 16.36 | Remained OCV% | 99.82% | | | | | | |
| Sample No.: 07 | | | | Sample No.: 08 | | | | | | | | | | | | |
| | Before | After | variation | Results | | Before | After | variation | Results | | | | | | | |
| Mass(g) | 234.3 | 234.3 | Mass loss % | 0.00% | P | Mass(g) | 234.3 | 234.3 | Mass loss % | 0.00% | P | | | | | |
| OCV(V) | 8.01 | 7.98 | Remained OCV% | 99.63% | | OCV(V) | 16.30 | 16.27 | Remained OCV% | 99.82% | | | | | | |
| T.5 External Short Circuit | | | | Start time: 5/22/ 13 : 52 | Finish time: 5/23/ 17 : 31 | Ambient temp.: 20.3 ℃ | Operator :Betty | Reviewer:Esmond | | | | | | | | |
| | Sample No.: 01 | Sample No.: 02 | Sample No.: 03 | Sample No.: 04 | Sample No.: 05 | Sample No.: 06 | Sample No.: 07 | Sample No.: 08 | | | | | | | | |
| Resistance (<100mΩ) | 56.8 | 57.6 | 55.9 | 56.1 | 56.3 | 53.8 | 55.4 | 55.3 | | | | | | | | |
| OCV before test/ after short circuit(V) | 16.63 | 0.00 | 16.63 | 0.00 | 16.63 | 0.01 | 16.62 | 0.01 | 8.25 | 0.01 | 16.63 | 0.00 | 16.63 | 0.00 | 16.61 | 0.01 |
| Max Temp. (< 170℃) | 55.1 | 55.2 | 55.2 | 55.0 | 55.2 | 55.1 | 55.2 | 55.1 | | | | | | | | |
| Results | P | P | P | P | P | P | P | P | | | | | | | | |
| T.6 Impact (Component cell) | | | | Start time: 5/9/ 03 : 21 | Finish time: 5/10/ 04 : 33 | Ambient temp.: 28.6 ℃ | Operator :Betty | Reviewer:Esmond | | | | | | | | |
| | Sample No.: 01 | Sample No.: 02 | Sample No.: 03 | Sample No.: 04 | Sample No.: 05 | | | | | | | | | | | |
| OCV before test(V) | 3.80 | 3.79 | 3.80 | 3.80 | 3.79 | | | | | | | | | | | |
| Max Temp. (< 170℃) | 110.5 | 108.7 | 108.4 | 106.7 | 105.4 | | | | | | | | | | | |
| Results | P | P | P | P | P | | | | | | | | | | | |
| | Sample No.: 06 | Sample No.: 07 | Sample No.: 08 | Sample No.: 09 | Sample No.: 10 | | | | | | | | | | | |
| OCV before test(V) | 3.79 | 3.80 | 3.79 | 3.79 | 3.80 | | | | | | | | | | | |
| Max Temp. (< 170℃) | 93.6 | 96.3 | 91.7 | 92.8 | 93.2 | | | | | | | | | | | |
| Results | P | P | P | P | P | | | | | | | | | | | |
| T.7 Overcharge | | | | Start time: 5/17/ 10 : 21 | Finish time: 5/18/ 16 : 26 | Ambient temp.: 27.3 ℃ | Operator :Betty | Reviewer:Esmond | | | | | | | | |
| | Sample No.: 09 | Sample No.: 10 | Sample No.: 11 | Sample No.: 12 | Sample No.: 13 | Sample No.: 14 | Sample No.: 15 | Sample No.: 16 | | | | | | | | |
| OCV before test(V) | 16.62 | 16.6 | 16.63 | 16.64 | 16.63 | 16.63 | 16.62 | 16.62 | | | | | | | | |
| Results | P | P | P | P | P | P | P | P | | | | | | | | |



新普科技股份有限公司
新世電子(常熟)有限公司
新普科技(重慶)有限公司
兆普電子(上海)有限公司

Control Number : SACU1205002

7. Equipment for test:



本資料為新普科技股份有限公司之智慧財產權，非經本公司書面授權許可，不得透露或使用本資料，亦不得複印、複製或轉變成其它任何形式使用。
The information contained herein is the exclusive property of SIMPLO TECHNOLOGY CO., LTD, and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission.

本測試報告僅對上述測試項目有效,本報告分離使用無效
This test report is valid only to the items, Invalid for separation using.