

W-TOUCH ultra-slim touchscreen system





www.aures.com







POSLIGNE

This 'all-in-one' touchscreen system is fanless and features a slimline design as well as a splash-proof front. Easy to install anywhere and ideal for wall-mounted till operations, it can also be mounted on a pole (or placed on a stand).

W-Touch is an integrated 15-inch touchscreen system that is just 48mm thick. Designed particularly for wall-mounted till applications, it can also be supplied on its stand or pole.

The system is fanless, dust-resistant and splash-proof, offering protection against water and other liquids. The front face complies with IP65 standards, so the system is ideal for use in harsh environments. **W-Touch** is powered by an **INTEL Pineview Dual Core D525** processor, ensuring optimum energy use. Mounting the system on a wall or a pole saves a considerable amount of space, so **W-Touch** is perfect for all types of sales and service outlets where space is at a premium. It's ideal for retail, takeaway sales, catering and kitchen environments, fast food outlets and mini-markets, as well as food and non-food self-serve stores.

The system can also be easily integrated and adapted to both checkout and selfcheckout terminal furniture. **W-Touch** incorporates the HSD Exclusive (*Hardware Status Display*) systems management solution. This multilingual utility allows users to receive key system data (such as processor temperature) in real time by means of automated e-mail alerts.

W-Touch is available in two colours: graphite black and pure white.

W-TOUCH compact and stylish

W-TOUCH

- Wall-mounted, integrated touchscreen system with VESA fixings – also available on its stand and for pole-mounted installation
- INTEL Pineview Dual Core D525 processor
- Integrated HSD Exclusive Solution for preventive maintenance and secured control of data
- Fanless system making it the perfect option for harsh environments
- Splash-proof, IP 65 standard front face
- HDD on removable rack
- Optional SSD flash drive

MODEL

Optimised energy consumption



MODEL	Wiooch
Processor	INTEL Pineview Dual Core D525
Chipset	CPU with Graphic built-in + ICH 8M
RAM	SO DIMM DDR3 2 GB expandable to 4 GB (2 slots)
Graphics memory	Up to 256 MB shared RAM
Hard drive	SATA 2.5" 160 GB hard drive on removable rack
Flash Memory	optional SSD SATA flash drive
Touch screen	Turbo Touch 15" Resistive
Brightness	250cd/sqm (250nits)
Resolution	1024 x 768
INPUTS / OUTPUTS	
Serial/COM	4 ports (2 self-powered)
USB 2.0	4 USB 2.0 ports
Parallel port	1 Sub-D 25 pin connector
LAN 10/100/1000	1 x RJ45
Cash drawer output	1 x RJ11 (12V/24V)
Mike input	1
Audio output	1
Additional video output	1
Mini PCIe slot	1
OTHER FEATURES	
Power supply	external, 90W, 19V, 4.7A
Operating temperature	5°C to 35°C (41° F to 95° F)
Storage temperature	-20° to 55° C (-4° F to 140° F)
IP 65 standard	Dust and splash-proof front face
Humidity rating (in operation)	20% to 80% (RH without condensation)
Humidity rating (in storage)	20% to 85% (RH without condensation)
Dimensions (W x H x D)	362 x 280 x 48 mm (excluding wall bracket)
Fixings	VESA 100 x 100 mm – may be used on a wall-mounted bracket or on a pedestal or stalk.
Weight	7kg
Compatible operating systems	Windows 7 , Windows XP Pro, WIN 2000/NT 4.0, POS Ready, Vista, Linux
HSD Exclusive	integrated solution for preventive maintenance and secured data
Options	SSD flash drive
Colours	Graphite black and pure white
	· ·



Slim Design



Inputs/ outputs





VESA holdings

